






Sylbek Firewall Hardware Platform



Page 1 / 2 For more information click on product image	Product Name / Platform	Storage CPU Memory	Network Ports Driver	Dimensions WxDxH Weight Noise Power consumpt.(idle)	Warranty Certificatess	I/O Ports	Test Status TCP-Throughput (Red -> Green)				
							IPCop v2.0.2	IPFire v2.11	pfSense v2.0.1	SmoothWall v3.0 sp3	Endian Comm. v2.5
	SBR116-FW i386, intel 945GSE	Atom N270 1.6 GHz 512MB SODIMM (Max 2GB) 1GB SLC 44pin IDE-Flash (Option 2x 2,5" SATA + 2x USB HDD)	3x GBit Ethernet 2x Intel PRO/1000, 1x RTL8111DL (Free Mini PCIe 30x50.95mm)	218x190x62 mm 1.4 kg, noiseless , 13 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 1x VGA 1x DVI 3x USB	compatible 370 MBit	compatible 370 MBit	compatible 220 MBit	compatible 250 MBit	compatible 250 MBit
	SBR216-FW i386, intel 945GC	1GB SLC SATA-Flash (Option 2,5" HDD) Dual Atom 330 2x1.6 GHz 512MB DDR2 (Max 2GB)	3x GBit Ethernet 2x Intel PRO/1000, 1x RTL8111C	311x241x65 mm 2.5 kg, ~ 27 db, 29 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA 6x USB 1x COM	compatible 540 MBit	compatible 680 MBit	compatible 350 MBit	compatible 480 MBit	compatible 480 MBit
	SBR217-FW i386, intel NM10	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Dual Atom D510 2x1.66 GHz 1GB DDR2 (Max 4GB)	3x GBit Ethernet 2x Intel PRO/1000, 1x RTL8111DL (Free Mini PCIe 30x50.95mm)	311x241x65 mm 2.5 kg, noiseless , 19 w 483x300x44 mm 6 kg, ~ 28 db, 23 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA 6x USB 1x COM	compatible 680 MBit	compatible 680 MBit	compatible 420 MBit	compatible 480 MBit	compatible 480 MBit
	SBR217-1U-FW	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)									
	SBR218-FW i386, intel NM10	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Dual Atom D525 2x1.8 GHz 1GB DDR2 (Max 4GB)	2x GBit Ethernet PCIe 2x RTL8111DL (2x Free Mini PCIe 30x50.95mm)	311x241x65 mm 2.5 kg, noiseless , 19 w 483x300x44 mm 6 kg, ~ 28 db, 23 w	36 months CE, FCC, RoHS, WEEE	2x RJ45 1x PS/2 1x VGA 1x HDMI 6x USB	compatible 690 MBit	compatible 690 MBit	compatible 430 MBit	compatible 690 MBit	compatible 690 MBit
	SBR218-1U-FW	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)									
	SBR220-FW i386, AMD Hudson M1	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Dual AMD Zacate E-350 1GB DDR3 (Max 8GB)	2x GBit Ethernet PCIe 2x RTL8111E Option SBR221 3x PCIe GBit Ethernet 2x Intel 82571EB , 1x RTL8111E	311x241x65 mm 2.5 kg, ~ 28 db, 21 w 483x220x44 mm 4.6 kg, ~ 31 db, 25 w	36 months CE, FCC, RoHS, WEEE	2x RJ45 1x PS/2 1x VGA DVI+HDMI 6x USB	compatible 760 MBit	compatible 760 MBit	not compatible	not compatible	compatible 250 MBit !
	SBR220-1U-FW	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)									
	SBR310-FW i386, intel G31	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Dual Pentium E5700 2x3.0 GHz 1GB DDR2 (Max 4GB)	3x GBit Ethernet 2x Intel PRO/1000, 1x RTL8111DL Option SBR311 3x PCIe GBit Ethernet 2x Intel 82571EB , 1x RTL8111DL	311x241x65 mm 2.5 kg, ~ 27 db, 24 w 483x220x44 mm 4.6 kg, ~ 30 db, 28 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA 1x COM 4x USB	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit
	SBR310-1U-FW	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)									
	SBR410-FW i386, intel G41	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Dual Pentium E5700 2x3.0 GHz 1GB DDR3 (Max 8GB)	3x GBit Ethernet 2x Intel PRO/1000, 1x RTL8111DL Option SBR411 3x PCIe GBit Ethernet 2x Intel 82571EB , 1x RTL8111DL	311x241x65 mm 2.5 kg, ~ 27 db, 26 w 483x220x44 mm 4.6 kg, ~ 30 db, 30 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA 1x COM 4x USB	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit	compatible 690 MBit compatible 820 MBit
	SBR410-1U-FW	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)									

Page 2 / 2 For more information click on product image	Product Name / Platform	Storage CPU Memory	Network Ports Driver	Dimensions WxDxH Weight Noise Power consumpt.(idle)	Warranty Certificatess	I/O Ports	Test Status TCP-Throughput (Red -> Green)				
							IPCop v2.0.2	IPFire v2.11	pfSense v2.0.1	SmoothWall v3.0 sp3	Endian Comm. v2.5
	SBR453-FW	1GB SLC 44pin IDE-Flash, (Option 2x 2,5" SATA + 2x USB HDD) Dual Core Mobile 2x 1.83 GHz 1GB (Max 2GB)	3x PCIe GBit Ethernet 3x Intel PRO/1000 (82573L)	311x241x65 mm 2.5 kg, ~ 28 db, 18 w 483x220x44 mm 4.6 kg, ~ 30 db, 23 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA 1x COM 2x USB	compatible	compatible	compatible	compatible	compatible
	i386, intel 945GM	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)					840 MBit	840 MBit	840 MBit	840 MBit	840 MBit
SBR453-1U-FW											
	SBR460-1U-FW	Dual Pentium 2x1.8 GHz 1GB (Max 4GB) 80GB 3.5" SATA HDD (Option 2nd 3,5" SATA HDD)	4x GBit Ethernet 4x Intel PRO/1000 (2xPCIe 82573L 2x 82546EB)	483x580x44 mm 12 kg, ~ 65 db, 55 w	36 months CE, FCC, RoHS, WEEE	4x RJ45 2x PS/2 1x VGA 1x COM 2x USB	compatible	compatible	compatible	not compatible	compatible
	i386 intel 946GZ						820 MBit	820 MBit	820 MBit	820 MBit	820 MBit
	SBR611-FW	1GB SLC SATA-Flash (Option 2,5" SATA HDD) Intel Pentium G860 2x3.0 GHz 2GB DDR3 (Max 16GB)	3x PCIe GBit Ethernet 2x Intel PRO/1000 82571EB 1x RTL8111E	311x241x65 mm 2.5 kg, ~ 25 db, 19 w 483x220x44 mm 4.6 kg, ~ 28 db, 23 w	36 months CE, FCC, RoHS, WEEE	3x RJ45 2x PS/2 1x VGA HDMI 4x USB	compatible	compatible	not compatible	not compatible	compatible
i386, intel H61	250GB 2.5" SATA HDD (Option 2nd 2,5" HDD)	830 MBit					830 MBit	830 MBit	830 MBit		
SBR611-1U-FW											

Sylbek Firewall Platform - Desktop, 311x241x65mm



© www.sylbek.eu You may use this graphic for any purpose, if you leave the copyright in place.

Sylbek Firewall Platform - 19" 1U, 483x220x44mm



© www.sylbek.eu You may use this graphic for any purpose, if you leave the copyright in place.

Sylbek Firewall Hardware Platform

Prices do not include VAT and shipping costs

Product Name	Sylbek Shop 1 pc	Sylbek Shop 3 pcs	Reseller
SBR116-FW	359 €	335 € / 7,2 %	ask
SBR216-FW	359 €	329 € / 9,1 %	ask
SBR217-FW	349 €	319 € / 9,4 %	ask
SBR217-1U-FW	429 €	399 € / 7,5 %	ask
SBR218-FW	409 €	375 € / 9,1 %	ask
SBR218-1U-FW	479 €	445 € / 7,6 %	ask
SBR220-FW	399 €	365 € / 9,3 %	ask
SBR220-1U-FW	468 €	435 € / 7,6 %	ask
SBR221-FW	459 €	425 € / 8 %	ask
SBR221-1U-FW	528 €	495 € / 6,7 %	ask
SBR310-FW	429 €	395 € / 8,6 %	ask
SBR310-1U-FW	485 €	449 € / 8 %	ask
SBR311-FW	489 €	455 € / 7,5 %	ask
SBR311-1U-FW	545 €	509 € / 7,1 %	ask
SBR410-FW	429 €	395 € / 8,6 %	ask
SBR410-1U-FW	485 €	449 € / 8 %	ask
SBR411-FW	489 €	455 € / 7,5 %	ask
SBR411-1U-FW	545 €	509 € / 7,1 %	ask
SBR453-FW	490 €	455 € / 7,7 %	ask
SBR453-1U-FW	539 €	499 € / 8 %	ask
SBR460-1U-FW	499 €	469 € / 6,4 %	ask
SBR611-FW	559 €	525 € / 6,5 %	ask
SBR611-1U-FW	635 €	595 € / 6,7 %	ask